



ANTIMOULD EMULSION

Description

An excellent, premium quality, low odour antimould coating guaranteed to protect against unsightly and unhygienic black mould even when there is persistent condensation. The unsurpassed performance is achieved by combining modern paint technology with highly advanced, proven biocides. The antimould biocide is combined throughout the paint film, which is formulated to impart toughness, elasticity, water resistance and durability to the finish.

Ideal for walls and ceilings in private and social housing and a wide range of public and commercial buildings. It is fully washable and resistant to the effects of condensation when the coating is fully dried out.

Properties

- **Guaranteed for a minimum of FIVE YEARS to prevent the recurrence of black mould**
- **Quick drying with no overpainting problems; compatible with all known paint finishes**
- **Approved under HSE Control of Pesticides 1986 Regulations as a surface biocide treatment against mould growth**
- **Easy to use and cost effective**

The Antimould Emulsion will help compliance with Section 82 (Statutory Nuisance), Chapter 43 of the Environmental Protection Act 1990, either used alone or part of various strategies to prevent condensation and mould growth in both private and public tenanted accommodation.

Restoration UK Ltd offer the reassurance of a full technical support and advisory service for condensation and mould growth to assist with specification queries or general problems.

Preparation

1. Remove any loose material such as old paint, grease, dirt, mould or defective wallpaper. **Surface Cleanser** can be used for "wetting in" purposes when removing wallpaper.
 2. Make good any defects in the surface and rub down to a smooth finish.
 3. Wash and clean all surfaces (walls, ceilings, window frames and joinery) using **Surface Cleanser**. If necessary clean badly affected areas a second time.
 4. Allow to dry thoroughly.
 5. If necessary, apply an appropriate primer or sealer to new, unprimed or porous plaster and wooden surfaces or bare metal.
 6. For new or porous plaster surfaces use **Antimould Emulsion** thinned up to 10% with clean tap water as normal good practice. Allow to dry thoroughly.
- After priming metal surfaces should be painted with two coats **Acrylic Gloss(P)**.

Application

1. Apply **Antimould Emulsion** using brush or roller.
2. **STIR THOROUGHLY BEFORE USE.**
3. Apply two coats **Antimould Emulsion** allowing sufficient drying time between coats.
4. Clean equipment with clean tap water before the paint dries.

N.B. If an unfinished, textured wallpaper (blown vinyl, woodchip) or similar is to be used then it should be hung after the **Surface Cleanser** has fully dried. The wallpaper should be coated with **Antimould Emulsion** as above.

Product Information

Coverage: 10-12 m² per litre but an extra allowance should be made for rough or porous surfaces.

Drying Time: Touch dry in 1 hour and recoatable after 2-4 hours dependent on conditions.

Thinning: Use clean tap water but do not exceed 10% by volume.

Uses: Can be used as a primer and undercoat for **Acrylic Eggshell (P)** or **Acrylic Gloss (P)**.

Colours: Brilliant White, Magnolia and selected pastel colours. Specific colours may be supplied depending upon requirements.

Packaging: 2.5 and 5.0 litres in HPDE containers.

Storage: Store above 5°C in dry conditions. Keep the container tightly sealed and away from children.

Shelf Life: Correctly stored, the unopened product has a shelf life of 12 months.

Health and Safety

The product is approved under the Control of Pesticides Regulations 1986 for use as directed (HSE No. 6308). In use the product is very similar to conventional high quality emulsion paint; refer to Safety Data Sheet (SDS) before using the product.

Information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that products, techniques and codes of practice are under constant review and changes occur without notice, please ensure you have the latest updated information.

Restoration UK Ltd
Unit 3, 18 Hanford Way
Loughborough
Leicestershire LE11 1LS
Web: www.restorationuk.com Email: info@restorationuk.com
Tel: 01509 217750